FORMATION REPORT INFORMATION REPORT

CENTRAL INTELLIGENCE AGENCY

This	material	contains	information	affecting the	Nat	ional Defense	of th	e United	States	withi	n th	e meaning	of the	Espionage	Laws,	Title
18,	U.S.C. S	ecs. 793	and 794, th	he transmissio	n or	revelation of	which	in any	manne	to	an	unauthorized	person	is prohibi	ted by	law.

	C-O-N-P-I-D-R-	N-T-I-A-L]	f. 1	RR
COUNTRY	USER (Moscow Oblast)	REPORT				
UBJECT	Marpov Pharmaceutical Plant in Moscow	DATE DISTR.	25 Pc	progry	1960	50X1-HL
		NO. PAGES	1			
						(
DATE OF					5	OX1-HUM
PLACE & DATE ACQ						XX
	SOURCE EVALUATIONS ARE DEFINITIVE. APPE	AISAL OF CONTEN	T IS TENT	ATIVE.	G	The Land
	Pharmaceutical Plant in Moscow with a splant and sketch of two used at this factory.	a report on ketch and leg unidentified	end of	the		50X1-HI
	plant and sketch of two	ketch and leg	end of	the		50X1-HU
	plant and sketch of two	ketch and leg	end of	the		50X1-HU
	plant and sketch of two	ketch and leg	end of	the		50X1-HU
	plant and sketch of two	ketch and leg	end of	the		50X1-HU
	plant and sketch of two	ketch and leg unidentified	end of	the		50X1-HU 50X1-HU 50X1-HU



STATE ARMY NAVY AIR FBI AEC ORR X

(Note: Washington distribution indicated by "X"; Field distribution by "#".)

Sanitized Copy Approved for Release 2010/09/16: CIA-RDP80T00246A052900550001-4

Sanitized Copy Approved for Release 2010/09/16 : CIA-RDP80T00246A052900550001-4

The Karpov Pharmaceutical Plant was located in the southern section of the city of Moseow on Regatinskoye sheese, in the Moskvoretskiy rayon near reka Moskva, and was subordinate to the Ministry of Health. The plant occupied a large area of unknown size, and was surreunded by an approximately three-meter high fence of stone mesonry along the west side of the plant, from the personnel gate to the west corner of the plant, and a wooden fence along the rest of the plant perimeter.

Description of the Plant Buildings

- 2. The majority of the plant structures were one story high and measured 40 meters by 15 meters. The buildings were of brick and reinferced consrete construction and were very fire-resistant. The numbers in parentheses below refer to sketch No. 1 of the plant layout on page 6: 50X1-HUM
 - (1) Work glothing supply building. The work clothes of the plant laborers
 - (2) Machine department building. Approximately 200 persons, including machine fitters, milling machine operators, lathe turners, electricians and

50X1-HUM

	C-O-N-F-I-D-E-N-T-I-A-L	
•		50X1-HUN
	-2-	23/(17101
	in this shop. Four work benches with m	
located immediately in machines	side the entrance to the shop. Many lati	hes and cutting in the shop. 50X1.
	vided into brigades under an unidentified This shop made new parts for plant	d shop chief.
The machine shop was p	provided with the damaged part and a sket-	
	shed, the part was given to the brigade	
he knew that machine a	e of replacing the part in the damaged me	t when a heavy
	to be moved for repairs. In this case, kery was located would take measures so the	
personnel would see or	ly the machine to be repaired, and leave	
work was completed.		50X1-
Department No. one. 7	his building was referred to only	
ie. one	a machine referred to as aparat	zhieh ennesmed
to be a beater or mixe		
	the beater cylindrical	l in shape,
		hily
approximately two meters	ers in dismeter and two meters deep, probability and anti-	ably of east 50X1-
LION CONSTRUCTION AND	with approximately 50 millimeter fulck at	alls. A very
resistant putty-like a avoid contact between	with approximately 20 millimeter thick we substance was used the sides of the cylinder and the liquid	in order to to be deposited
resistant putty-like a avoid contact between	with approximately 20 millimeter thick we substance was used the sides of the cylinder and the liquid ined the inside walls of the cylinder.	in order to to be deposited 50X1
resistant putty-like a avoid contact between in the boiler (sic), l	with approximately 20 millimeter thick we ubstance was used the sides of the cylinder and the liquid ined the inside walls of the cylinder. three of these beaters placed in a state of the sides of the cylinder.	in order to to be deposited 50X1
resistant putty-like savoid contact between in the boiler (sic), leovered by floor-level	the sides of the cylinder and the liquid ined the inside walls of the cylinder. three of these beaters placed in a standard wooden planks in the first compartment of the cylinder.	in order to to be deposited 50X1 tone masonry pit of the shop
resistant putty-like a world contact between in the boiler (sic), l covered by floor-level building. The planks	with approximately 20 millimeter thick we ubstance was used the sides of the cylinder and the liquid ined the inside walls of the cylinder. three of these beaters placed in a state of the sides of the cylinder.	in order to to be deposited 50X1 tone masonry pit of the shop pair men could
resistant putty-like savoid contact between in the boiler (sic), leavered by floor-level building. The planks descend into the pit.	with approximately 20 millimeter thick we ubstance was used the sides of the cylinder and the liquid ined the inside walls of the cylinder. three of these beaters placed in a standard were removed so that the Machine Shop repartment of the the repairs were completed as a woman, dressed in white smocks, test	in order to to be deposited 50X1- tone masonry pit of the shop pair men could five or the boiler
resistant putty-like savoid contact between in the boiler (sic), leavered by floor-level building. The planks descend into the pit.	with approximately 20 millimeter thick we ubstance was used the sides of the cylinder and the liquid ined the inside walls of the cylinder. three of these beaters placed in a standard were removed so that the Machine Shop repartment of the repairs were completed.	in order to to be deposited 50X1- tone masonry pit of the shop pair men could five or the boiler
resistant putty-like savoid contact between in the boiler (sic), leavered by floor-level building. The planks descend into the pit.	with approximately 20 millimeter thick we ubstance was used the sides of the cylinder and the liquid ined the inside walls of the cylinder. three of these beaters placed in a standard were removed so that the Machine Shop repartment of the the repairs were completed as a woman, dressed in white smocks, test	in order to to be deposited 50X1- tone masonry pit of the shop pair men could five or the boiler
resistant putty-like savoid contact between in the boiler (sic), leavered by floor-level building. The planks descend into the pit.	with approximately 20 millimeter thick we ubstance was used the sides of the cylinder and the liquid ined the inside walls of the cylinder. three of these beaters placed in a standard were removed so that the Machine Shop repartment of the the repairs were completed as a woman, dressed in white smocks, test	in order to to be deposited 50X1- tone masonry pit of the shop pair men could five or the boiler
resistant putty-like savoid contact between in the boiler (sic), leavered by floor-level building. The planks descend into the pit. six persons, one of the basing by controlling building No. two.	with approximately 20 millimeter thick we was used the sides of the cylinder and the liquid ined the inside walls of the cylinder. three of these beaters placed in a standard ware removed so that the Machine Shop repartment of the repairs were completed as a woman, dressed in white smocks, test the flow of steam and water into the cylinder.	in order to to be deposited 50X1 tone masonry pit of the shop pair men could five or the boiler sed approximately
resistant putty-like savoid contact between in the boiler (sic), leavered by floor-level puilding. The planks descend into the pit. Six persons, one of the basing by controlling building No. two. Building No. two. Building No. two. Building No. two. Building No. (See	with approximately 20 millimeter thick we caused the sides of the cylinder and the liquid ined the inside walls of the cylinder. three of these beaters placed in a standard ware removed so that the Machine Shop repartment of the repairs were completed as a woman, dressed in white smocks, test the flow of steam and water into the cylinder sketch on page of for descriptions.	in order to to be deposited 50X1 tone masonry pit of the shop pair men could five or the boiler sed approximately
resistant putty-like savoid contact between in the boiler (sic), leavered by floor-level puilding. The planks descend into the pit. Six persons, one of the basing by controlling building No. two. Building No. two. Building No. two. Building No. two. Building No. (See	with approximately 20 millimeter thick we calculated was used the sides of the cylinder and the liquid ined the inside walls of the cylinder. three of these beaters placed in a standard water placed in a standard were removed so that the Machine Shop repartment of the repairs were completed was a woman, dressed in white smocks, test the flow of steam and water into the cylinder flow of steam and water into the cylinder sketch on page of for descripts in the middle of the shop floor.	in order to to be deposited 50X1 tone masonry pit of the shop pair men could five or the boiler Inder sed approximately ption of these 50X1
resistant putty-like a world contact between in the boiler (sic), leovered by floor-level building. The planks lescend into the pit. six persons, one of the masing by controlling building No. two.	with approximately 20 millimeter thick was used the sides of the cylinder and the liquid ined the inside walls of the cylinder. three of these beaters placed in a statement of the removed so that the Machine Shop removed so that the Machine Shop removed so that the Machine Shop removed as woman, dressed in white smocks, test the flow of steam and water into the cylinder of the flow of steam and water into the cylinder in the middle of the shop floor. The lower part of these boilers	in order to to be deposited 50X1 tone masonry pit of the shop pair men could five or the boiler sed approximately option of these 50X1
resistant putty-like a swoid contact between in the boiler (sic), leavered by floor-level building. The planks descend into the pit. Six persons, one of the hasing by controlling the boilers (See levices) placed in row thipped often, perhaps were located in a pit	with approximately 20 millimeter thick we calculated was used the sides of the cylinder and the liquid ined the inside walls of the cylinder. three of these beaters placed in a standard water placed in a standard were removed so that the Machine Shop repartment of the repairs were completed was a woman, dressed in white smocks, test the flow of steam and water into the cylinder flow of steam and water into the cylinder sketch on page of for descripts in the middle of the shop floor.	in order to to be deposited 50X1 tone masonry pit of the shop pair men could five or the boiler sed approximately ption of these 50X1 s or receptacles and. The boilers
resistant putty-like a world contact between in the boiler (sic), leavered by floor-level building. The planks descend into the pit. Six persons, one of the masing by controlling building No. two. Building No.	with approximately 20 millimeter thick was used the sides of the cylinder and the liquid ined the inside walls of the cylinder. three of these beaters placed in a statement of the removed so that the Machine Shop removed so that the Machine Shop removed so that the Machine Shop removed as a woman, dressed in white smocks, test the flow of steam and water into the cylinder flow of steam and water into the cylinder in the middle of the shop floor. The lower part of these boilers due to acid action, and had to be replaced.	in order to to be deposited 50X1 tone masonry pit of the shop pair men could five or the boiler sed approximately ption of these 50X1 or receptacles ped. The boilers had no
resistant putty-like a swoid contact between in the boiler (sic), leavered by floor-level pullding. The planks descend into the pit. Six persons, one of the hasing by controlling the boilers (See devices) placed in row whipped often, perhaps were located in a pit subdivisions.	was used the sides of the cylinder and the liquid ined the inside walls of the cylinder. three of these beaters placed in a standard water placed in a standard were removed so that the Machine Shop repartment of the repairs were completed as a woman, dressed in white smocks, test the flow of steam and water into the cylinder sketch on page if for descripts in the middle of the shop floor. The lower part of these boilers and on also on floor level. The building and on also on floor level.	in order to to be deposited 50X1- tone masonry pit of the shop pair men could five or the boiler sed approximately ption of these 50X1 s or receptacles the boilers had no
resistant putty-like a world contact between in the boiler (sic), leovered by floor-level building. The planks lescend into the pit. Six persons, one of the mains by controlling the boilers (See levices) placed in row whipped often, perhaps were located in a pit subdivisions.	with approximately 20 millimeter thick was used the sides of the cylinder and the liquid ined the inside walls of the cylinder. three of these beaters placed in a statement of the removed so that the Machine Shop removed so that the Machine Shop removed so that the Machine Shop removed as a woman, dressed in white smocks, test the flow of steam and water into the cylinder flow of steam and water into the cylinder in the middle of the shop floor. The lower part of these boilers due to acid action, and had to be replaced.	in order to to be deposited 50X1 tone masonry pit of the shop pair men could five or the boiler sed approximately oution of these 50X1 s or receptacles red. The boilers had no 50X1-
resistant putty-like a woid contact between in the boiler (sic), leovered by floor-level building. The planks descend into the pit. Six persons, one of the masing by controlling the boilers (See devices) placed in row whipped often, perhaps were located in a pit subdivisions. Soilers' Building. The soilers' Building.	was used the sides of the cylinder and the liquid ined the inside walls of the cylinder. three of these beaters placed in a standard water placed in a standard were removed so that the Machine Shop repartment of the repairs were completed as a woman, dressed in white smocks, test the flow of steam and water into the cylinder sketch on page if for descripts in the middle of the shop floor. The lower part of these boilers and on also on floor level. The building and on also on floor level.	in order to to be deposited 50X1 tone masonry pit of the shop pair men could five or the boiler sed approximately option of these 50X1 s or receptacles and. The boilers had no 50X1- 50X
resistant putty-like a woid contact between in the boiler (sic), leovered by floor-level building. The planks descend into the pit. Six persons, one of the masing by controlling the boilers (See devices) placed in row whipped often, perhaps were located in a pit subdivisions. Soilers' Building. The soilers' Building.	was used the sides of the cylinder and the liquid ined the inside walls of the cylinder. three of these beaters placed in a state was used in three of these beaters placed in a state was a woman, in the first compartment of were removed so that the Machine Shop remarks were completed as a woman, dressed in white smocks, test the flow of steam and water into the cylinder of the flow of steam and water into the cylinder in the middle of the shop floor. The lower part of these boilers due to acid action, and had to be replaced and on also on floor level. The building is structure was located about 200 meters as a structure was located about 200 meters and is structure was located about 200 meters.	in order to to be deposited 50X1- tone masonry pit of the shop pair men could five or the boiler sed approximately ption of these 50X1 or receptacles sed. The boilers had no 50X1- from building steam flowed, liding No. one.

,	Release 2010/09/16 : CIA-RDP80T00246A05	
· · ·	C-O-N-F-I-D-E-N-T-I-A-L	
	0-0-R-Y-J-B-B-Y-T-X-D	
	-3-	50X1-Hl
,		30/1-110
Unidentified two-s	tory structure.	
	ians worked in it. Its personnel did hour as the laborers.	not leave the
Storehouse.	the doors were always close	
wide platform with Offices. This was	dilding, and parallel to it, a one-met a a smooth cement surface was used for a three-story building which occupie wribed above. Many persons worked in	truck loading. 50X
		50X1-HU
Married couples' 1	iving quarters.	
) Bechelors' living	quarters.	
		is I sould not be
identified	licated by a question mark on sketch R	50X1-HI
	r Supply	50X1
equate for plant need ter was from the regul ter deposits in the p	re small, the 110/220 volt current useds. The electric power never was cut clar Moscow city water supply. There plant area.	off The were no emergency
ter was from the regular deposits in the pansportation	is. The electric power never was cut that Moscow city water supply. There plant area.	off The
ter was from the regular deposits in the pansportation	is. The electric power never was cut that Moscow city water supply. There	The were no emergency 50X1-
ter was from the regular deposits in the panaportation leks from an outside oplant had no trucks	is. The electric power never was cut clar Moscow city water supply. There plant area. source transported plant products.	The were no emergency
ter was from the regular deposits in the pansportation leks from an outside e plant had no trucks by plant vehicle	is. The electric power never was cut clar Moscow city water supply. There plant area. source transported plant products. s of its own or a garage. The plant of	The were no emergency 50X1- irector used the 50X1-
ter was from the regular deposits in the pansportation leks from an outside e plant had no trucks by plant vehicle	is. The electric power never was cut clar Moscow city water supply. There plant area. source transported plant products.	The were no emergency 50X1- irector used the 50X1-

3•

4.

5•

6.

C-O-N-F-I-D-E-N-1	<u>'-1-A-L</u>
1 12	
-4-	
	50X1-
windows inmachine shop were too high outside.	to see what was goint on
Working Conditions	50X1-
Plant working hours were as follows: technic until 1200 hours and from 1300 hours until 16 personnel worked from 0800 hours until 1300 hours in the afternoon. Since some technical an unidentified building, and for hours repair shop brigade remained after 1700 hours breakdowns.	600 hours. Laborers and office hours and from 1400 until 1700 personnel worked after hours in a permanent machine
Vacation Periods	
Annual vacation periods of one month duration	
sonnel. Individual vacation dates were set a individual employee's wishes.	
sonnel. Individual vacation dates were set a	
sonnel. Individual vacation dates were set a individual employee's wishes.	coording to plant needs and the
sonnel. Individual vacation dates were set a individual employee's wishes. Salaries Plant employees received a type of salary advof each month and the balance of the salary was a salary with the salary was a sal	coording to plant needs and the
sonnel. Individual vacation dates were set a individual employee's wishes. Salaries Plant employees received a type of salary advof each month and the balance of the salary wonth. Plant Security Two blue-uniformed guards, one located at the check each worker's prepared and the other states.	rance after the first fifteen daws.
sonnel. Individual vacation dates were set a individual employee's wishes. Salaries Plant employees received a type of salary advof each month and the balance of the salary wonth. Plant Security Two blue-uniformed guards, one located at the check each worker's propusk and the other at plant in the daytime. a few other	rance after the first fifteen daws ras received at the end of the 50X1 repersonnel entrance in order to the vehicle entrance guarded this guards with pistols near the
sonnel. Individual vacation dates were set a individual employee's wishes. Salaries Plant employees received a type of salary advof each month and the balance of the salary wonth. Plant Security Two blue-uniformed guards, one located at the check each worker's propusk and the other at plant in the daytime. a few other plant wall.	rance after the first fifteen daws. Tas received at the end of the 50X1 The personnel entrance in order to the vehicle entrance guarded the guards with pistols near the 50X1
sonnel. Individual vacation dates were set a individual employee's wishes. Salaries Plant employees received a type of salary advof each month and the balance of the salary wonth. Plant Security Two blue-uniformed guards, one located at the check each worker's propusk and the other at plant in the daytime. a few other plant wall.	rance after the first fifteen daws. Tas received at the end of the 50X1 The personnel entrance in order to the vehicle entrance guarded the guards with pistols near the 50X1 50X1
sonnel. Individual vacation dates were set a individual employee's wishes. Salaries Plant employees received a type of salary advof each month and the balance of the salary wonth. Plant Security Two blue-uniformed guards, one located at the check each worker's propusk and the other at plant in the daytime. Organization and Personnel Organization and Personnel	rance after the first fifteen daws. Tas received at the end of the 50X1 The personnel entrance in order to the vehicle entrance guarded the guards with pistols near the 50X1 50X1
sonnel. Individual vacation dates were set a individual employee's wishes. Salaries Plant employees received a type of salary advof each month and the balance of the salary wonth. Plant Security Two blue-uniformed guards, one located at the check each worker's propusk and the other at plant in the daytime. Organization and Personnel Organization and Personnel	rance after the first fifteen daws. Tas received at the end of the 50X1 The personnel entrance in order to the vehicle entrance guarded the guards with pistols near the 50X1 50X1

	.052900550001-4
Release 2010/09/16 : CIA-RDP80T00246A	332333331 H
C-O-N-R-T-D-E-N-T-I-A-L	
-5-	
Lant director.	
	50X1-HU
	c-c-N-R-I-D-E-N-T-I-A-L -5- Lant director.

C-O-N-F-I-D-E-N-T-I-A-L

50X1-HUM

50X1-HUM



